




Speed, Performance, Value - The Right Balance

- Stainless steel pan
- Auto power off
- Low battery indication
- ShockProtect™ overload three-point protection
- Can be stacked for storage (120mm pan size only)
- Lock down mounting slot for Kensington™ type lock and cable
- Dual Tare keys, colour-coded for easy recognition
- Removable draught shield (120mm pan size only)
- Below balance weighing with hanger
- Backlit LCD display
- Mains adapter supplied as standard
- Weighing
- Below balance weighing



Technical Specifications

Model	CQT 202	CQT 251	CQT 601	CQT 1501	CQT 2601	CQT 2000	CQT 5000
Maximum capacity	200g	250g	600g	1500g	2600g	2000g	5000g
Readability	0.01g	0.1g	0.1g	0.1g	0.1g	1g	1g
Repeatability (S.D.)	0.02g	0.1g	0.1g	0.1g	0.1g	1g	1g
Linearity (±)	0.02g	0.1g	0.1g	0.2g	0.2g	1g	1g
Typical stabilisation time	3 Sec	2 Sec		3 Sec			2 Sec
Draught shield dimensions	-				-		
Pan size	120mm Ø				145mm Ø		

General Specifications

Units of measurement	Kilogram (kg), Gram (g), Pound (lb), Ounce (Oz), Carat (ct), Dram (d), Grain (GN), Newton (N)
Operating temperature	0°C 40°C
Power supply	12VAC 15mA
Overall dimensions (wxdxh)	173x255x86mm
Net weight	0.9kg

Key Accessories

- Security Lock and Cable
- Hard Carry Case with Lock
- In-use Cover



Adam Equipment - offices worldwide

www.adamequipment.com