Highland™ Portable Precision Balances





Speed, Performance, Value - The Right Balance

- RS232 and USB Interface both included
- Can be stacked for storage (120mm pan size only)
- ShockProtect[™] overload three-point protection
- Handical[™] manual internal calibration with built-in mass
- Lock down mounting slot for Kensington[™] type lock and cable
- Dual Tare keys, colour-coded for easy recognition
- Capacity tracker
- Removable draught shield (120mm pan size only)
- · Stainless steel pan
- Auto power off

- Low battery indication
- Adjustable levelling feet
- Rechargeable battery / mains adapter supplied as standard
- Below balance weighing with hanger
- Backlit LCD display
- Weighing
- Percentage weighing
- Parts counting
- Below balance weighing
- Weight accumulation









www.adamequipment.com



Technical Specifications

Model	HCB 123	HCB 153	HCB 302	HCB	HCB 602	HCB	НСВ	HCB
				602H		1002	1502	3001
Maximum capacity	120g	150g	300g	600g	600g	1000g	1500g	3000g
Readability	0.001g	0.005g	0.01g	0.01g	0.02g	0.01g	0.05g	0.1g
Repeatability (S.D.)	0.003g	0.005g	0.01g	0.1g	0.02g	0.02g	0.05g	0.1g
Linearity (±)	0.003g	0.01g	0.02g	0.02g	0.02g	0.02g	0.1g	0.2g
Pan size	120mm Ø							
Net weight	2kg						1.5kg	2kg

General Specifications

Typical stabilisation time	2 Sec
Operating temperature	0°C 40°C
Power supply	12VDC 800mA
Draught shield	Removable draft shield standard on all models
Draught shield	132mm
dimensions	
Overall dimensions	172×251×75mm
(wxdxh)	

Key Accessories

- · RS-232 Cable
- Hard Carry Case with Lock
- · Security Lock and Cable
- · Adam Printer
- AdamDU Data Collection Program





Adam Equipment - offices worldwide

www.adamequipment.com